Alltrack Rail Co Pty Ltd
alltrackrail.com.au
sales@alltrackrail.com.au
Phone: +61 459 575 798

2005 Komatsu PC138US-2E1 Hi-Rail Excavator – Broad & Standard Gauge



2005 Komatsu PC138US-2E1 tracked hi-rail excavator configured for operation on both broad and standard gauge rail networks.

The machine combines a compact-radius hydraulic excavator with hi-rail equipment for road-rail operation. It is described as suitable for rail maintenance, construction, infrastructure works and confined work areas.

The excavator is powered by a Komatsu SAA4D95LE-3 series turbocharged diesel engine with an approximate rated output of 66.2 kW. The standard machine operating weight is approximately 13,400 kg, while the rail-equipped weight is approximately 14,200 kg depending on the rail gear, attachments and machine configuration.

The machine is located in Rutherford, NSW. ONRSR notification is stated in the source. Inspection and confirmation of individual machine specifications is recommended.

SPECIFICATIONS

Specification	Details
General & Dimensions	
Builder / Manufacturer	Komatsu
Model	PC138US-2E1

Alltrack Rail Co Pty Ltd
alltrackrail.com.au
sales@alltrackrail.com.au
Phone: +61 459 575 798

SPECIFICATIONS

General & Dimensions	
Year Manufactured	2005
Machine Type	Hi-Rail Excavator
Serial Number	KMTPC043C01004642
Condition	Used (Inspection Recommended)
Quantity Available	1
Track Gauge	1435 mm – Standard Gauge, 1600 mm – Broad Gauge
Operating / Service Weight	Approx. 13,400 kg standard machine; rail-equipped weight approx. 14,200 kg depending on configuration
Length	Approx. 7,260 mm
Width	Approx. 2,490–2,515 mm
Height	Approx. 2,850 mm
Listing Reference	75001
Powerplant & Performance	
Engine	Komatsu SAA4D95LE-3 series turbocharged diesel engine
Power	Approx. 66.2 kW / 89 hp
Additional Details	
Features	Broad and standard gauge hi-rail configuration; tracked undercarriage; compact tail-swing design; hydraulic excavator functionality combined with rail capability
Compliance / Certification	ONRSR notified
Additional Information	Generic model specifications: maximum digging depth approx. 5,480 mm; maximum digging height approx. 9,340 mm. Dimensions and weights are manufacturer's/base-model specifications and may vary due to the fitted hi-rail system, attachments and machine configuration. Inspection and confirmation of individual machine specifications is recommended.

Alltrack Rail Co Pty Ltd
alltrackrail.com.au
sales@alltrackrail.com.au
Phone: +61 459 575 798

SPECIFICATIONS

Location	
Country	Australia
State / Region	NSW
General Location	Rutherford, NSW
Inspection Available	Inspection recommended